SUNPAR 125



000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

SECTION 1. IDENTIFICATION

Product name : SUNPAR 125

Synonyms : Product code: 100751

Manufacturer or supplier's details

HollyFrontier Specialty Products 1700 South Union Avenue

Tulsa OK 74107 United States

Telephone: Customer Service: (800) 456-4786

Emergency telephone number

Emergency telephone : CHEMTREC: 1-800-424-9300; CCN: 999116

number Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Process Oil

Prepared by : Product Safety

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Product code: 100751

CAS-No. : 64742-65-0

Page: 1 / 12

SUNPAR 125



000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), solvent-	64742-65-0	100
dewaxed heavy paraffinic; Baseoil —		
unspecified		

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do NOT use water jet.

Specific hazards during

firefighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HE SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material.

Non-sparking tools should be used.

Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

None known.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition.

Keep container closed when not in use.

Do not handle at temperatures >40°C, unless wearing

appropriate protective equipment.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Page: 3 / 12

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HF SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : slight

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HF SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Odour Threshold : No data available

pH : Not applicable

Pour point : $<= -12 \,^{\circ}\text{C} \, (<= 10 \,^{\circ}\text{F})$

Boiling point/boiling range : 294 - 633 °C (561 - 1171 °F)

Flash point : $>= 196 \, ^{\circ}\text{C} \, (>= 385 \, ^{\circ}\text{F})$

Method: Cleveland open cup

Fire Point : No data available

Evaporation rate : No data available

Flammability : Remarks: No data available

Auto-Ignition Temperature : 675 °F / 357 °C

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : < 0.000013 kPa (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : $0.87 (61 \,^{\circ}\text{F} / 16 \,^{\circ}\text{C})$

Density : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

log Pow: 2 - 6

Viscosity

Viscosity, kinematic : > 25 cSt (104 °F / 40 °C)

> 4.6 cSt (212 °F / 100 °C)

> 128 sus (100 °F / 38 °C)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

Molecular weight : > 378 g/mol

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous : Hazardous polymerisation does not occur.

Page: 5 / 12

SUNPAR 125



000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

reactions Stable under normal conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Reactive with oxidising agents.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks : Non-irritating to the skin. Heated material can cause thermal

burns

Serious eye damage/eye irritation

Product:

Remarks : Non-irritating to the eyes. Heated material can cause thermal

burns.

Respiratory or skin sensitisation

Product:

Exposure routes: Skin contact

Species: Guinea pig

Result: Not a skin sensitizer.

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HF SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Remarks: No evidence of skin sensitization.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: Not considered to be a germ cell mutagen.

Carcinogenicity

Product:

Remarks : The mineral oils in the product contain < 3% DMSO extract (IP

346). Not considered to be carcinogenic.

Reproductive toxicity

Product:

Effects on fertility : Remarks: Not considered to be toxic to the reproductive

system.

Effects on foetal development

: Remarks: Not considered to be teratogenic.

STOT - single exposure

Product:

Remarks : Acute exposure studies show no evidence of systemic toxicity.

STOT - repeated exposure

Product:

Remarks : Repeat dose toxicity data shows no evidence of target organ

toxicity.

Aspiration toxicity

Product:

Not expected to be an aspiration hazard.

Further information

Product:

Remarks : Prolonged or repeated contact can defat the skin and lead to

irritation, cracking and/or dermatitis.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Page: 7 / 12

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HE SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): > 100 mg/l

Exposure time: 72 h

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC (Daphnia (water flea)): > 1 mg/l

Exposure time: 21 d

Persistence and degradability

Product:

Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

This product has no known ecotoxicological effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

Page: 8 / 12

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HE SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

Contaminated packaging : Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

Not applicable

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic; 64742-65-0

Baseoil — unspecified:

Pennsylvania Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic; 64742-65-0

Baseoil — unspecified

New Jersey Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic; 64742-65-0

Baseoil — unspecified

New York City Hazardous Substances

Distillates (petroleum), solvent-dewaxed heavy paraffinic; 64742-65-0

Baseoil — unspecified

California Prop. 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

SUNPAR 125



000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AIIC : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory


EINECS : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

Page: 10 / 12

SUNPAR 125

HOLLYFRONTIER SPECIALTY PRODUCTS AN HE SINCLAIR BRAND

000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Product Safety

Revision Date : 2023/03/29 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

SAFETY DATA SHEET SUNPAR 125



000003010003

Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Page: 12 / 12