



2780 Waterfront Parkway E Dr, Indianapolis, IN 46214.

Product Data Sheet

Product : HYDROCAL 60
Revised Date : 2018-08-16
Product Code : 300727052000

Test	UOM	Description	Method Description	Min	Max	Typical
API GRAVITY @ 60°F			D4052	26.0	28.0	27.8
COLOR, ASTM			D1500		0.5	0.5
VISCOSITY @ 40°C	cSt		D445			10.10
VISCOSITY @ 100°F	SUS		D2161	60.0	65.0	62.0
VISCOSITY @ 210°F	SUS		D2161			34.6
VISCOSITY INDEX			D2270			54
FLASH POINT, COC	°C		D92	138		149
FLASH POINT, COC	°F		D92	280		300
POUR POINT	°F		D97		-70	-71
POUR POINT	°C		D97		-57	-57
ANILINE POINT	°F		D611			170.0
ANILINE POINT	°C		D611			76.6
REFRACTIVE INDEX @ 20°C			D1218			1.4800

External Notes

DISTRIBUTED BY: R.E. CARROLL, INC. 1570 NORTH OLDEN AVENUE EXT. TRENTON N.J. 08638 USA
T: 609-695-6211/800-257-9365 F: 609-695-0102 Orders@recarroll.com

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.