

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068

Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

### SECTION 1. IDENTIFICATION

Product name : SUNDEX 790TN

Synonyms : Extracts (petroleum), heavy paraffinic distillate solvent  
Product code: 100813

#### Manufacturer or supplier's details

HollyFrontier Specialty Products  
1700 South Union Avenue  
Tulsa OK 74107  
United States  
Telephone : Customer Service: (800) 456-4786

#### Emergency telephone number

Emergency telephone number : CHEMTREC: 1-800-424-9300; CCN: 999116  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : Process Oil

Prepared by : Product Safety

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure : Category 1 (Adrenal gland, Bone marrow, Kidney, Liver, lymphatic system, Stomach, thymus)

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : May cause cancer.  
Suspected of damaging the unborn child.  
Causes damage to organs (Adrenal gland, Bone marrow, Kidney, Liver, lymphatic system, Stomach, thymus) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

understood.  
Do not breathe mist or vapours.  
Wash skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

IF exposed or concerned: Get medical advice/ attention.

### Storage:

Store locked up.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Extracts (petroleum), heavy paraffinic distillate solvent  
Product code: 100813

CAS-No. : 64742-04-7

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Extracts (petroleum), heavy paraffinic distillate solvent	64742-04-7	100

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

- |   |   |   |
|---|---|---|
| In case of skin contact                                     | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Wash clothing before reuse.<br>Seek medical advice. |
| In case of eye contact                                      | : | Remove contact lenses.<br>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Obtain medical attention.   |
| If swallowed  | : | Rinse mouth with water.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Never give anything by mouth to an unconscious person.<br>Seek medical advice.   |
| Most important symptoms and effects, both acute and delayed | : | First aider needs to protect himself.   |
| Notes to physician  | : | Treat symptomatically.  |

---

### SECTION 5. FIREFIGHTING MEASURES

- |   |   |  |
|---|---|--|
| Suitable extinguishing media                  | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| Unsuitable extinguishing media                | : | Do NOT use water jet.  |
| Specific hazards during firefighting          | : | Cool closed containers exposed to fire with water spray.   |
| Hazardous combustion products                 | : | Carbon oxides (CO, CO <sub>2</sub> ), smoke and irritating vapours as products of incomplete combustion. |
| Further information                           | : | Prevent fire extinguishing water from contaminating surface water or the ground water system.            |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary.                                   |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Ensure adequate ventilation.<br>Evacuate personnel to safe areas.<br>Material can create slippery conditions.<br>Mark the contaminated area with signs and prevent access to unauthorized personnel.<br>Only qualified personnel equipped with suitable protective equipment may intervene. |
|---|---|---|

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : None known.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.  
Do not handle at temperatures >40°C, unless wearing appropriate protective equipment.
- Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Extracts (petroleum), heavy paraffinic distillate solvent	64742-04-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

- Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

contaminants.

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection  
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use.  
Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : dark

Odour : slight

Odour Threshold : No data available

pH : Not applicable

Pour point :  $\leq 24\text{ }^{\circ}\text{C}$  ( $\leq 75\text{ }^{\circ}\text{F}$ )

Boiling point/boiling range :  $289 - 602\text{ }^{\circ}\text{C}$  ( $552 - 1116\text{ }^{\circ}\text{F}$ )

Flash point :  $\geq 162\text{ }^{\circ}\text{C}$  ( $\geq 324\text{ }^{\circ}\text{F}$ )  
Method: Pensky-Martens closed cup

Fire Point : No data available

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

Evaporation rate	:	No data available
Flammability	:	Remarks: No data available
Auto-Ignition Temperature	:	$\geq 700$ °F / $\geq 371$ °C
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	$< 0.000013$ kPa (100.0 °F / 37.8 °C)
Relative vapour density	:	No data available
Relative density	:	0.97 (61 °F / 16 °C)
Density	:	No data available
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	log Pow: $\geq 4$
Viscosity Viscosity, kinematic	:	$\geq 24.4$ cSt (104 °F / 40 °C)
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Molecular weight	:	$\geq 278$ g/mol

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

### Acute toxicity

#### Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

#### Components:

##### **Extracts (petroleum), heavy paraffinic distillate solvent:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg,

### Skin corrosion/irritation

#### Product:

Remarks : Slightly irritating to the skin. Heated material can cause thermal burn.

### Serious eye damage/eye irritation

#### Product:

Remarks : May cause slight transient irritation. Heated material can cause thermal burns.

### Respiratory or skin sensitisation

#### Product:

Remarks: No evidence of skin sensitization.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: Not considered to be a germ cell mutagen.

### Carcinogenicity

#### Product:

Remarks : Cancer hazard, based on skin-painting studies using laboratory animals, involving continuous, long-term contact. IARC: Group 1. Risk of cancer depends on duration and level or exposure.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: Suspected of damaging fertility.

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

Effects on foetal development : Remarks: Suspected of damaging the unborn child.

### STOT - single exposure

#### Product:

Remarks : Acute exposure studies show no evidence of systemic toxicity.

### STOT - repeated exposure

#### Product:

Remarks : Causes damage to organs through prolonged or repeated exposure.  
Category 1 - adrenal, bone marrow, kidneys, liver, lymphatic system, stomach, thymus

### Aspiration toxicity

#### Product:

Not expected to be an aspiration hazard.

### Further information

#### Product:

Remarks : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

#### Components:

##### **Extracts (petroleum), heavy paraffinic distillate solvent :**

Toxicity to fish : EC50 (Fish): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 35.9 mg/l  
Exposure time: 48 h



# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

Toxicity to algae/aquatic plants : EC50 (algae): 18.8 mg/l  
Exposure time: 96 h

### Persistence and degradability

#### Product:

Biodegradability : Result: Inherently biodegradable.

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : This product has no known ecotoxicological effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

Contaminated packaging : Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### National Regulations

#### **49 CFR**

Not regulated as a dangerous good

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

### SECTION 15. REGULATORY INFORMATION

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Water Act

Not applicable

#### US State Regulations

##### Massachusetts Right To Know

Extracts (petroleum), heavy paraffinic distillate solvent: 64742-04-7

##### Pennsylvania Right To Know

Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7

##### New Jersey Right To Know

Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7

##### New York City Hazardous Substances

Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7

#### California Prop. 65

WARNING: This product can expose you to chemicals including polycyclic aromatic compounds (benzo(a)pyrene), which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The components of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AIIC : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

EINECS : On the inventory, or in compliance with the inventory

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29


Print Date 2023/03/29

TCSI : On the inventory, or in compliance with the inventory

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

# SAFETY DATA SHEET

## SUNDEX 790TN

000003010068



Version 2.1

Revision Date 2023/03/29

Print Date 2023/03/29

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Product Safety

Revision Date : 2023/03/29

Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN