SA	FE.	TY C)AT	A S	ΗE	EΤ
----	-----	------	-----	-----	----	----

SUNDEX 750T

000003010042

Version 2.1

Revision Date 2023/03/29



Print Date 2023/03/29

SECTION 1. IDENTIFICATION

Manufacturer or supp	Product code: 100809
Product name Synonyms	 SUNDEX 750T Extracts (petroleum), heavy paraffinic distillate solvent

	HollyFrontier Specialty Products
	1700 South Union Avenue
	Tulsa OK 74107
	United States
Telephone :	Customer Service: (800) 456-4786

Emergency telephone number

Emergency telephone num-	:	CHEMTREC: 1-800-424-9300; CCN: 999116
ber		Poison Control Centre: Consult local telephone directory for
		emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use	:	Process Oil
Prepared by	:	Product Safety

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	:	Category 1B
Reproductive toxicity	:	Category 2
Specific target organ toxicity - repeated exposure	:	Category 1 (Adrenal gland, Bone marrow, Kidney, Liver, lym- phatic system, Stomach, thymus)
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May cause cancer. Suspected of damaging the unborn child. Causes damage to organs (Adrenal gland, Bone marrow, Kid- ney, Liver, lymphatic system, Stomach, thymus) through pro- longed or repeated exposure.
Precautionary statements	:	Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapours.

SUNDEX 750T

000003010042



rsion 2.1	Revision Date 2023/03/29	Print Date 2023/03/29
	Wash skin thoroughly after handli Do not eat, drink or smoke when Wear protective gloves/ protective protection.	using this product.
	Response: IF exposed or concerned: Get me	dical advice/attention
	Storage: Store locked up.	
	Disposal: Dispose of contents/ container to plant.	an approved waste disposal
Other hazards None known.		
IARC	No component of this product pres or equal to 0.1% is identified as pr firmed human carcinogen by IARC	obable, possible or con-
OSHA	No component of this product pres equal to 0.1% is on OSHA's list of	
NTP	No component of this product presequal to 0.1% is identified as a know by NTP.	

Substance / Mixture Substance name	-	Substance Extracts (petroleum), heavy paraffinic distillate solvent Product code: 100809
CAS-No.	:	64742-04-7

Components

Chemical name	CAS-No.	Concentration (% w/w)
Extracts (petroleum), heavy paraffinic	64742-04-7	100
distillate solvent		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	 Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized

SUNDEX 750T

000003010042



Version 2.1	Revision Date 2023/03/29	Print Date 2023/03/29
	skin cleanser.	
	Wash clothing before reuse. Seek medical advice.	
In case of eye contact	: Remove contact lenses.	
in case of eye contact	Rinse immediately with plenty of for at least 15 minutes. Obtain medical attention.	water, also under the eyelids,
If swallowed	 Rinse mouth with water. DO NOT induce vomiting unless cian or poison control center. Never give anything by mouth to Seek medical advice. 	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himse	elf.
Notes to physician	: Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	Do NOT use water jet.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

SUNDEX 750T

000003010042



000003010042		
Version 2.1	Revision Date 2023/03/29	Print Date 2023/03/29
fire and explosion		
Advice on safe handling	 For personal protection see section Smoking, eating and drinking shown plication area. Use only with adequate ventilation in case of insufficient ventilation, vequipment. Avoid contact with skin, eyes and Do not ingest. Keep away from heat and sources in the container closed when not in the container closed when closed	uld be prohibited in the ap- n. wear suitable respiratory clothing. s of ignition. n use.
Conditions for safe storage	Do not handle at temperatures >4 priate protective equipment. Store in original container. Containers which are opened mus kept upright to prevent leakage. Keep in a dry, cool and well-ventil Keep in properly labelled containe To maintain product quality, do no	st be carefully resealed and lated place. ers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

light.

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis				
Extracts (petroleum), heavy	64742-04-7							
paraffinic distillate solvent								
		late matter)						
		TWA (Mist)	5 mg/m3	OSHA Z-1				
		TWA (Mist)	5 mg/m3	OSHA P0				
		TWA (Mist)	5 mg/m3	NIOSH REL				
		ST (Mist)	10 mg/m3	NIOSH REL				
Engineering measures	should be su contaminants	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.						
Personal protective equipme	ent							
Respiratory protection	ventilation is that exposure Respirator se exposure lev	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.						
Filter type	•	organic vapour filter						
Hand protection	. organio vapo							
Material	: neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .							
Remarks	approved sta	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-						
Eye protection		Wear face-shield and protective suit for abnormal processing						
		Page: 1 / 11						

SUNDEX 750T

000003010042



Version 2.1		Revision Date 2023/03/29	Print Date 2023/03/29
Skin and body protection	:	Choose body protection in relation tration and amount of dangerous s cific work-place.	
Protective measures Hygiene measures		Wash contaminated clothing befor Remove and wash contaminated ing the inside, before re-use. Wash face, hands and any expose handling.	clothing and gloves, includ-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	:	liquid dark slight No data available
рН	:	Not applicable
Pour point	:	<= 24 °C (<= 75 °F)
Boiling point/boiling range	:	289 - 602 °C (552 - 1116 °F)
Flash point	:	>= 162 °C (>= 324 °F) Method: Pensky-Martens closed cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Remarks: No data available
Auto-Ignition Temperature	:	>= 700 °F / >= 371 °C
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	< 0.000013 kPa (100.0 °F / 37.8 °C)
Relative vapour density	:	No data available
Relative density	:	0.97 (61 °F / 16 °C)
Density	:	No data available
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water Viscosity	:	log Pow: >= 4
Viscosity, kinematic	:	>= 24.4 cSt (104 °F / 40 °C)
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SUNDEX 750T

000003010042



Version 2.1 Revision D

Revision Date 2023/03/29

Print Date 2023/03/29

Molecular weight : >= 278 g/mol

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	Heat, flames and sparks. Reactive with oxidising agents. Under normal conditions of storage and use, hazardous de- composition products should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

|--|

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Components:

Extracts (petroleum), heavy paraffinic distillate solvent:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks : Slightly irritating to the skin. Heated material can cause thermal burn.

Serious eye damage/eye irritation

Product:

Remarks	:	May cause slight transient irritation.	Heated material can
		cause thermal burns.	

Respiratory or skin sensitisation

SAFETY DATA SHEET HOLLYER SPECIALTY PRODUCTS SUNDEX 750T AN HF SINCLAIR BRAND 000003010042 Version 2.1 Revision Date 2023/03/29 Print Date 2023/03/29 Product: Remarks: No evidence of skin sensitization. Germ cell mutagenicity **Product:** Genotoxicity in vitro : Remarks: Not considered to be a germ cell mutagen. Carcinogenicity Product: Remarks Cancer hazard, based on skin-painting studies using laborato-: ry animals, involving continuous, long-term contact. IARC: Group 1. Risk of cancer depends on duration and level or exposure. **Reproductive toxicity Product:** Effects on fertility Remarks: Suspected of damaging fertility. : Effects on foetal develop-Remarks: Suspected of damaging the unborn child. : ment STOT - single exposure Product: Remarks Acute exposure studies show no evidence of systemic toxicity. STOT - repeated exposure **Product:** Remarks Causes damage to organs through prolonged or repeated 1 exposure. Category 1 - adrenal, bone marrow, kidneys, liver, lymphatic system, stomach, thymus Aspiration toxicity Product: Not expected to be an aspiration hazard. **Further information Product:** Remarks Prolonged or repeated contact can defat the skin and lead to · irritation, cracking and/or dermatitis.

SUNDEX 750T

000003010042

Version 2.1



Print Date 2023/03/29

SECTION 12. ECOLOGICAL INFORMATION

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants		Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available

Components:

Extracts (petroleum), heavy paraffinic distillate solvent :

Toxicity to fish	:	EC50 (Fish): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): 35.9 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): 18.8 mg/l Exposure time: 96 h

Persistence and degradability

Product:

Biodegradability	:	Result: Inherently biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-	:	This product has no known ecotoxicological effects.
mation		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
Contaminated packaging	: Do not re-use empty containers.

SUNDEX 750T

000003010042

Version 2.1

Revision Date 2023/03/29

HOLLYFRONTIER SPECIALTY PRODUCTS AN HF SINCLAIR BRAND

Print Date 2023/03/29

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards :	Carcinogenicity Reproductive toxicity Specific target organ toxicity (single	e or repeated exposure)	
SARA 313 :	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.		
Clean Water Act			
Not applicable			
US State Regulations			
Massachusetts Right To Know	1		
Extracts (petroleum),	heavy paraffinic distillate solvent:	64742-04-7	
Pennsylvania Right To Know			
Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7			
New Jersey Right To Know			
Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7			
New York City Hazardous Substances			
Extracts (petroleum), heavy paraffinic distillate solvent 64742-04-7			
California Prop. 65	WARNING: This product can expose you to chemicals includ- ing polycyclic aromatic compounds (benzo(a)pyrene), which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.		
The components of this produ	ct are reported in the following inv	entories:	
TSCA :	All chemical substances in this pro-	duct are either listed on the	

SUNDEX 750T

000003010042



Version 2.1	Revision Date 2023/03/29	Print Date 2023/03/29
AIIC :	TSCA Inventory or are in compliance we exemption. On the inventory, or in compliance with	
DSL :	On the inventory, or in compliance with	the inventory
KECI :	On the inventory, or in compliance with	the inventory
PICCS :	On the inventory, or in compliance with	the inventory
IECSC :	On the inventory, or in compliance with	the inventory
NZIoC :	On the inventory, or in compliance with	the inventory
EINECS :	On the inventory, or in compliance with	the inventory
TCSI :	On the inventory, or in compliance with	the inventory

SECTION 16. OTHER INFORMATION

Further information

NFPA 704: HMIS® IV: Flammability HEALTH * 1 FLAMMABILITY 1 Health Instability 1 0 **PHYSICAL HAZARD** 0 HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents Special hazard the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded

SUNDEX 750T

000003010042

Version 2.1

Revision Date 2023/03/29

HOLLY FRONTIER SPECIALTY PRODUCTS AN HF SINCLAIR BRAND

Print Date 2023/03/29

		at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Prepared by	:	Product Safety
Revision Date Date format	-	2023/03/29 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.