



# R.E. Carroll, Inc.

Fillers • Extenders • Oils • Lubricants

1570 North Olden Avenue, Trenton, New Jersey 08638-3204  
(800) 257-9365 • (609) 695-6211 • Fax (609) 695-0102  
Kent, Ohio (330) 724-8284 • Fax (330) 724-3311  
[www.recarroll.com](http://www.recarroll.com)

## Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.  
Customer Service and Technical Service can be reached at 1-800-437-3188.

Product: **Calsol 875**

Product Code: **2070-00-P**

Revised: 01/03/2006

HazMat Name: Non-Regulated

STCC: 29-114-15

<u>Test</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
Viscosity, CST @ 40C	D445	139.00	157.00	148.10
Viscosity, CST @ 100C	D445			10.44
Viscosity, SUS @ 100F	D2161	750.0	850.0	797.1
Viscosity, SUS @ 210F	D2161			62.0
Gravity, API, 60F	D4052	18.5	22.0	21.3
Flash Point, COC, C	D92	199		204
Flash Point, COC, F	D92	390		399
Pour Point, C	D97		-15	-22
Pour Point, F	D97		5	-8
Color, ASTM	D1500		12.0	1.0
Aniline Point, C	D611		87.8	86.0
Aniline Point, F	D611		190	186.8
Neut. No., MG KOH/G	D974		0.030	0.011
Viscosity-Gravity Constant	D2501			0.867
Refractive Index @ 20 C	D1218			1.5054