



Product Data Sheet

Product: **CALSOL 5550**
 Revised: **07/20/2015**
 HazMat Name: **Non-Regulated**

Product Code: **1650-00-P**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 40°C	cSt	D445	92.74	101.98	95.32
VISCOSITY @ 100°C	cSt	D445			9.03
VISCOSITY @ 100°F	SUS	D2161	490.0	540.0	503.4
VISCOSITY @ 210°F	SUS	D2161			56.8
API GRAVITY @ 60°F		D4052	24.8	26.0	25.3
FLASH POINT, COC	°C	D92	218		221
FLASH POINT, COC	°F	D92	425		430
POUR POINT	°C	D97		-12	-32
POUR POINT	°F	D97		10	-26
COLOR, ASTM		D1500		0.5	L0.5
ANILINE POINT	°C	D611	97.7	104.4	100.1
ANILINE POINT	°F	D611	208.0	220.0	212.1
NEUTRALIZATION NUMBER	mg KOH/g	D974			.012
VISCOSITY-GRAVITY CONSTANT		D2501	.830	.845	.840
REFRACTIVE INDEX @ 20°C		D1218			1.4913
UV ABSORPTIVITY, 260 NM		D2008		.6	.5

DISTRIBUTED BY: R.E. CARROLL, INC. 1570 NORTH OLDEN AVENUE, TRENTON NJ 08638-3204 USA
T: 609-695-6211/800-257-9365 F: 609-695-0102 www.recarroll.com