

**INDUSTRIAL RAW MATERIALS LLC**

112 West 56th Street, New York, NY 10019
T: (212) 688-8080 F: (212) 759-3696
sales@irmwax.com www.irmwax.com

DISTRIBUTOR:**R.E. CARROLL INC.**

1570 North Olden Ave.
Trenton, NJ 08638-3204
609-695-6211/800-257-9365
www.recarroll.com

INDRAWAX 6642

Indrawax 6642 is a petroleum slack wax. It can be used in candle wax blends, wax emulsions, wood and fibre board sizing, de-dusting for roofing granules, roads, fertilizer, glass wool, and textile treating, and other applications.

SPECIFICATIONS

Property	Method ASTM	Min	Max	Typical
Congealing point, °F (°C)	D-938	140.0 (60.0)	154.0 (67.8)	-
Penetration @ 77°F, dmm	D-1321	-	-	65
Oil content, wt%	D-721	-	10.0	-
Color, ASTM	D-1500	-	1.5	-
Viscosity @ 212°F, cSt	D-445	6.8	10.0	-
Flash point COC, °F (°C)	D-92	450 (232)	-	-

Every care has been taken in the presentation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Industrial Raw Materials LLC.