



Specifications for
RECCO 165 MICROCRYSTALLINE WAX

PROPERTIES GUARANTEED	TEST METHOD	LIMITS
Residue On Ignition	NF (Current Revision)	0.10 Max.
Organic Acids	NF (Current Revision)	PASS
Alkalinity	NF (Current Revision)	PASS
Acidity	NF (Current Revision)	PASS
Fixed Oils, Fats, and Rosin	NF (Current Revision)	PASS
Color	NF (Current Revision)	PASS
Residual Solvents, Reportable Quantity	USP 467	NONE
Melting Point, °C	ASTM D127	73.9/79.4
Melting Point, °F	ASTM D127	165/175
Penetration @ 77°F	ASTM D1321	60/80
Color, Saybolt	ASTM D156	+16 Min.
Viscosity @210°F, SUS	ASTM D2161	75/90
Odor Rating, Panel Average	LATM 093	1.0 Max.
Flash Point, COC, °F	ASTM D92	475 Min.

RECCO 165 is a Microcrystalline Wax NF meeting requirements for NF (current revision) and FDA requirements as per 21 CFR 172.886.

1/28/2013

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Safety Data Sheet (SDS) for this product. No warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to this product. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.