

SUPER WHITE PROTOPET® PETROLATUM

000003009659

rsion 1.2		Revision Date 2023/03/24	Print Date 2023/03/2		
131011 1.2		116VI31011 Date 2023/03/24	F IIII Date 2023/03/2		
CTION 1. IDENTIFICATION					
Product name	:	SUPER WHITE PROTOPET® PE	TROLATUM		
Synonyms	:	Product code: 216F			
Manufacturer or supplier's		ails Sonneborn, LLC 100 Sonneborn Lane Petrolia PA 16050 United States Security (24 hour): (724) 756-2210)		
Emergency telephone num	ber				
Emergency telephone num- ber	:	CHEMTREC: 1-800-424-9300; CC Poison Control Centre: Consult loc emergency number(s).			
Recommended use of the c	he	nical and restrictions on use			
Recommended use	:	: High purity Petrolatum is typically used as a blending base a variety of applications including cosmetic, pharmaceutica food and general industrial.			
Prepared by	:	Product Safety: +1-724-756-2210			

1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or con- firmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Substance
Substance name	: Product code: 216F



SUPER WHITE PROTOPET® PETROLATUM

000003009659

Version 1.2	Revision Date 2023/03/24	Print Date 2023/03/24

CAS-No. : 8009-03-8

Components

Chemical name	CAS-No.	Concentration (% w/w)
Petrolatum; Petrolatum	8009-03-8	100

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Dry chemical Carbon dioxide (CO2) Water fog Foam
Unsuitable extinguishing media	:	Do NOT use water jet.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.



000003009659

sonneborn
AN HF SINCLAIR BRAND

Version 1.2		Revision Date 2023/03/24	Print Date 2023/03/24	
Further information	:	 Prevent fire extinguishing water from contaminating surface water or the ground water system. 		
Special protective equipment for firefighters	:	Wear self-contained breathing apparate essary.	us for firefighting if nec-	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use. Do not handle at temperatures >40°C, unless wearing appro- priate protective equipment.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.



000003009659

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS	No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
Petrolatum; Petrolatum	8009	-03-8	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH	
			TWA (Mist)	5 mg/m3	OSHA Z-1	
			TWA (Mist)	5 mg/m3	OSHA P0	
			TWA (Mist)	5 mg/m3	NIOSH REL	
			ST (Mist)	10 mg/m3	NIOSH REL	
Engineering measures	shou		icient to control	nents. Good general worker exposure to a		
Personal protective equipm	ent					
Respiratory protection	: Use vent that Res expo	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.				
Filter type	: orga	organic vapour filter				
Hand protection Material	: neop	neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .				
Remarks	appı cher essa	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary. When handling hot material, use heat resistant gloves.				
Eye protection		Chemical splash goggles and a full-face shield should be worn when handling this material.				
Skin and body protection	tratio	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.				
Protective measures	: Was	sh contam	inated clothing b	pefore re-use.		
Hygiene measures	ing t Was	Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.				

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance



12

SUPER WHITE PROTOPET® PETROLATUM

000003009659

ersion 1.2		Revision Date 2023/03/24	Print Date 2023/03/24
Colour	:	White to light yellow	
Odour	:	Odourless or mild petroleum oil like.	
Odour Threshold	:	No data available	
рН	:	No data available	
Melting point/freezing point	:	35 - 80 °C (95 - 176 °F)	
Boiling point/boiling range	:	> 230 °C (> 446 °F)	
Flash point	:	> 93.4 °C (> 200.1 °F) Method: Pensky-Martens closed cup	
Fire Point	:	No data available	
Evaporation rate	:	No data available	
Flammability	:	Remarks: No data available	
Auto-Ignition Temperature	:	> 554 °F / > 290 °C	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	< 0.1 kPa (68 °F / 20 °C)	
Relative vapour density	:	No data available	
Relative density	:	< 1	
Density	:	0.75 - 0.87 g/cm3 (212 °F / 100 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	log Pow: > 6	
Viscosity Viscosity, kinematic	:	5 - 30 cSt (212 °F / 100 °C)	
Explosive properties	:	Do not pressurize, cut, weld, braze, so pose containers to heat or sources of	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.





000003009659

Version 1.2		Revision Date 2023/03/24	Print Date 2023/03/24	
Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occ Stable under normal conditions.	cur.	
Conditions to avoid	:	Heat, flames and sparks.		
Incompatible materials	:	Reactive with oxidising agents.		
Hazardous decomposition products	:	Under normal conditions of storage and composition products should not be pro		

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Eye contact Ingestion Inhalation Skin contact Acute toxicity **Product:** Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg, Acute inhalation toxicity : Remarks: No data available Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg, Skin corrosion/irritation Product: Remarks Non-irritating to the skin. Heated material can cause thermal 2 burns. Serious eye damage/eye irritation Product: Remarks Non-irritating to the eyes. Heated material can cause thermal 5 burns.

Respiratory or skin sensitisation

Product:

Exposure routes: Skin contact Species: Guinea pig Result: Not a skin sensitizer. Remarks: No evidence of skin sensitization.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: Not considered to be a germ cell mutagen.

Carcinogenicity





SUPER WHITE PROTOPET® PETROLATUM

000003009659

sion 1.2		Revision Date 2023/03/24	Print Date 2023/03
Product:			
Remarks	:	Classified as non-carcinogenic ba in Nota N (Regulation (EC) 1272/2 N).	
Reproductive toxicity			
Product:			
Effects on fertility	:	Remarks: Not considered to be to tem.	xic to the reproductive sys
Effects on foetal develop- ment	:	Remarks: Not considered to be te	ratogenic.
STOT - single exposure			
Product: Remarks	:	Acute exposure studies show no e	evidence of systemic toxic
STOT - repeated exposure			
Product:			
Remarks	:	Repeat dose toxicity data shows r toxicity.	no evidence of target orga
Aspiration toxicity			
Product:			
Not expected to be an aspira	ation	hazard.	

Ecotoxicity

Product:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/lExposure time: 72 h
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	ty	
Product:		
		

SUPER WHITE PROTOPET® PETROLATUM

000003009659

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

Bioaccumulative potential	
No data available	
Mobility in soil	
No data available	
Other adverse effects	
No data available	
SECTION 13. DISPOSAL CONSIDERATIONS	

Disposal methods

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed dis- posal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
Contaminated packaging	:	Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

49 CFR

Not regulated as a dangerous good

Remarks

: When transported above >100C – UN3257 ELEVATED TEMPERATURE LIQUIDS, N.O.S. (9), III, Class: 9 (M9), UN No.: 3257, Packaging Group: III, Hazard No.: 99, Label: 9, Technical Description: Petroleum Jelly, Freight Description Road: 65 Petroleum Oil, N.O.I.B.N.

SECTION 15. REGULATORY INFORMATION

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

000003009659



sonneborn
AN HF SINCLAIR BRAND

sion 1.2		Revision Date 2023/03/24	Print Date 2023/03/24
SARA 311/312 Hazards	:	No SARA Hazards	
		This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
US State Regulations			
Massachusetts Right To Petrolatum; Petr		1:	8009-03-8
Pennsylvania Right To K Petrolatum; Petr		I	8009-03-8
New Jersey Right To Kno Petrolatum; Petr		I	8009-03-8
New York City Hazardous Petrolatum; Petr			8009-03-8
California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm. For more information go to www.P65Warnings.ca.gov.	
The components of this	oroduo	are reported in the following inv	ventories:
TSCA	:	All chemical substances in this pro TSCA Inventory or are in complian exemption.	
AIIC	:	On the inventory, or in compliance	with the inventory
DSL	:	On the inventory, or in compliance	with the inventory
ENCS	:	On the inventory, or in compliance	with the inventory
KECI	:	On the inventory, or in compliance	with the inventory
PICCS	:	On the inventory, or in compliance	with the inventory
IECSC	:	On the inventory, or in compliance	with the inventory
NZIoC	:	On the inventory, or in compliance	with the inventory
EINECS	:	On the inventory, or in compliance	with the inventory
TCSI	:	On the inventory, or in compliance	with the inventory

SECTION 16. OTHER INFORMATION

Further information

SUPER WHITE PROTOPET® PETROLATUM

000003009659

Version 1.2





HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Table Z-1-A Limits for Air Contaminants (1989 vacated
	•	values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New

SUPER WHITE PROTOPET[®] PETROLATUM

000003009659

Version 1.2

Revision Date 2023/03/24

Print Date 2023/03/24

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Prepared by	:	Product Safety: +1-724-756-2210
Revision Date Date format	-	2023/03/24 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

