PARAFLEX ^{™/MC} HT 3



DISTRIBUTED BY: R.E. CARROLL, INC. 1570 NORTH OLDEN AVENUE EXT. EWING, NJ 08638-3204 USA T: 609-695-6211/800-257-9365 F: 609-695-0102 Orders@RECarroll.com

000003000159

Version 2.1

Revision Date 2019/01/15

Print Date 2019/01/15

SECTION 1. IDENTIFICATION

Product name :	PARAFLEX TM/MC HT 3
Product code :	PHT3DRM, PHT3DCT, PHT3, PHT3BLK
Manufacturer or supplier's deta	ails Petro-Canada America Lubricants LLC 115N Oak Park Avenue #1C Oak Park IL 60301-1366 United States
Emergency telephone number	
Emergency telephone number :	Petro-Canada Lubricants Inc.: +1 905-403-5770; CHEMTREC Transport Emergency: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the cher	nical and restrictions on use
Recommended use :	Paraflex HT oils are process oils used as a diluent or carrier in the production of a variety of finished industrial products.
Prepared by :	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Colour	Clear and bright
Odour	Mild petroleum oil like.

GHS classification in accordance with 29 CFR 1910.1200

:

Aspiration hazard	: Category 1	

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : May be fatal if swallowed and enters airways.

Precautionary statements

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Storage: Store locked up. Disposal:

PARAFLEX TM/MC HT 3

000003000159

-



Version 2.1	Revision Date 2019/01/15	Print Date 2019/01/15
	Dispose of contents/ container to a plant.	an approved waste disposal
Potential Health Effects		
Primary Routes of Entry	: Eye contact Ingestion Inhalation Skin contact	
Aggravated Medical Condi- tion	: None known.	
Other hazards None known.		
IARC	No component of this product presen equal to 0.1% is identified as probabl human carcinogen by IARC.	5
OSHA	No component of this product presen equal to 0.1% is identified as a carcir gen by OSHA.	
NTP	No component of this product presen equal to 0.1% is identified as a know by NTP.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	 Substance
	 Jubblance

Components

Chemical name	CAS-No.	Concentration (% w/w)
distillates (petroleum), hydrotreated	64742-55-8	100
light paraffinic		

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

PARAFLEX TM/MC HT 3

000003000159



Version 2.1	Revision Date 2019/01/15	Print Date 2019/01/15
	Obtain medical attention.	
If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless cian or poison control center. Never give anything by mouth to Seek medical advice.	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himse	elf.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Should not be released into the environment. Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : None known. fire and explosion Internet: lubricants.petro-canada.com/sds ™ Owned or used under license.

PARAFLEX TM/MC HT 3

000003000159



Version 2.1	Revision Date 2019/01/15	Print Date 2019/01/15
Advice on safe handling	For personal protection see section 8. Smoking, eating and drinking should b plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear equipment. Avoid contact with skin, eyes and cloth Do not ingest. Keep away from heat and sources of in Keep container closed when not in use	suitable respiratory ing. gnition.
Conditions for safe storage	 Store in original container. Containers which are opened must be kept upright to prevent leakage. Keep in a dry, cool and well-ventilated Keep in properly labelled containers. To maintain product quality, do not sto light. Keep locked up or in an area accessib authorised persons. 	place. re in heat or direct sun-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures	:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Personal protective equipme	ent	
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe-

PARAFLEX TM/MC HT 3



000003000159

Version 2.1		Revision Date 2019/01/15	Print Date 2019/01/15
		cific work-place.	
Protective measures	:	Wash contaminated clothing befor	e re-use.
Hygiene measures	:	Remove and wash contaminated of ing the inside, before re-use. Wash face, hands and any expose handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Clear and bright
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-24 °C (-11 °F)
Boiling point/boiling range	:	No data available
Flash point	:	124 °C (255 °F) Method: Pensky-Martens closed cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Auto-ignition temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.845 kg/l (15 °C / 59 °F)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, kinematic Internet: lubricants.petro-canada.com/s ™ Owned or used under license.	: ds	3.6 cSt (40 °C / 104 °F)

PARAFLEX TM/MC HT 3

000003000159



Version 2.1		Print Date 2019/01/15	
		1.30 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurise, cut, weld, braze, so pose containers to heat or sources of	
SECTION 10. STABILITY AND RE	AC	ΤΙVΙΤΥ	
Possibility of hazardous reac- tions	:	Hazardous polymerisation does not of Stable under normal conditions.	ccur.
Conditions to avoid	:	No data available	
Incompatible materials	:	Reactive with oxidising agents.	

Hazardous decomposition	: May release COx, smoke and irritating vapours when heate to decomposition.
products	to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of	:	Eye contact
exposure		Ingestion
		Inhalation
		Skin contact

Acute toxicity

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Components:

distillates (petroleum), hydro Acute oral toxicity	otre :	eated light paraffinic: LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,
Skin corrosion/irritation		

Product:

Remarks	: No data available

PARAFLEX TM/MC HT 3

000003000159

Version 2.1



Print Date 2019/01/15

Serious eye damage/eye irritation

Product:

Remarks

: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available

Persistence and degradability

Product:

Biodegradability	:	Remarks: No data available
------------------	---	----------------------------

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

PARAFLEX TM/MC HT 3

000003000159

Version 2.1



Print Date 2019/01/15

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm.		
The components of this product are reported in the following inventories:				
DSL	:	On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
IECSC	:	On the inventory, or in compliance with the inventory		
EINECS	:	On the inventory, or in compliance with the inventory		
AICS	:	On the inventory, or in compliance with the inventory		
KECI	:	On the inventory, or in compliance with the inventory		
PICCS	:	On the inventory, or in compliance with the inventory		

PARAFLEX ^{™/MC} HT 3


000003000159

Version 2.1

Print Date 2019/01/15

SECTION 16. OTHER INFORMATION

Further information



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

PARAFLEX TM/MC HT 3



000003000159

Version 2.1	Revision Date 2019/01/15	Print Date 2019/01/15	
For Copy of SDS	United States, telephone: 1-800 6285	 Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201-6285 For Product Safety Information: 1 905-491-0565 	
Prepared by	: Product Safety: +1 905-491-056	5	
Revision Date	: 2019/01/15		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN