PARAFLEX TM/MC HT 100

000003001345

Version 2.2	Revision Date 2019/09/17	Print Date 2019/09/17 PETROCANADA
SECTION 1. IDENTIFICATION		DISTRIBUTED BY: R.E. CARROLL, INC. 1570 N. OLDEN AVE., EWING, NJ 08638 609-695-6211/800-257-9365 Orders@RECarroll.com
Product name	PARAFLEX TM/MC HT 100	
Product code	: PHT100DRM, PHT100DC	T, PHT100, PHT100BLK
Manufacturer or supplier's de	tails	
	Petro-Canada America Lul 115N Oak Park Avenue #1 Oak Park IL 60301-1366 United States +1 888-284-4572	
Emergency telephone numbe	r	
Emergency telephone number		300; nsult local telephone directory for
Recommended use of the che	mical and restrictions on u	se
Recommended use :		ss oils used as a diluent or carrier in of finished industrial products.
Prepared by :	Product Safety: +1 905-49	1-0565

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Colour	Clear and bright
Odour	Mild petroleum oil like.

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry	: Eye contact Ingestion
	Inhalation
	Skin contact

Aggravated Medical Condi- : None known. tion

Other hazards

None known.

IARC

No component of this product present at levels greater than or



PARAFLEX TM/MC HT 100

PETRO CANADA

000003001345

Version 2.2	Revision Date 2019/09/17	Print Date 2019/09/17
	equal to 0.1% is identified as probable, po human carcinogen by IARC.	ssible or confirmed
OSHA	No component of this product present at le equal to 0.1% is identified as a carcinoger gen by OSHA.	
NTP	No component of this product present at le equal to 0.1% is identified as a known or a by NTP.	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
---------------------	---	-----------

Components

Chemical name	CAS-No.	Concentration (% w/w)
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	90 - 100

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media :

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

PARAFLEX TM/MC HT 100



000003001345

Version 2.2		Revision Date 2019/09/17	Print Date 2019/09/17
Unsuitable extinguishing media	:	No information available.	
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire	with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxi oxides (SOx), smoke and irritating vapo incomplete combustion.	
Further information	:	Prevent fire extinguishing water from co water or the ground water system.	ontaminating surface

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	None known.
Advice on safe handling :	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage :	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place.



000003001345



Version 2.2

Revision Date 2019/09/17

Print Date 2019/09/17

Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Engineering measures		ufficient to control	ments. Good general worker exposure to a	
Personal protective equipment	nt			
Respiratory protection	Use respirat ventilation is that exposu Respirator s exposure lev	s provided or expo res are within reco selection must be	ess adequate local e osure assessment de ommended exposure based on known or a of the product and the respirator.	monstrates guidelines. nticipated
Filter type	: organic vap	our filter		
Hand protection Material	: neoprene, n	itrile, polyvinyl alc	cohol (PVA), Viton(R)	
Remarks	approved st	andard should be	is gloves complying v worn at all times whe sessment indicates th	en handling
Eye protection	: Wear face-s problems.	hield and protecti	ve suit for abnormal p	processing
Skin and body protection		amount of danger	ation to its type, to th ous substances, and	
Protective measures	: Wash conta	minated clothing I	pefore re-use.	
Hygiene measures	ing the insid	e, before re-use.	ted clothing and glov	

PARAFLEX TM/MC HT 100

000003001345

Version 2.2

Revision Date 2019/09/17

Print Date 2019/09/17

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	:	viscous liquid	
Colour	:	Clear and bright	
Odour	:	Mild petroleum oil like.	
Odour Threshold	:	No data available	
рН	:	No data available	
Pour point	:	-15 °C (5 °F)	
Boiling point/boiling range	:	No data available	
Flash point	:	260 °C (500 °F) Method: Cleveland open cup	
Fire Point	:	No data available	
Evaporation rate	:	No data available	
Auto-ignition temperature	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	0.87 kg/l (15 °C / 59 °F)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Viscosity Viscosity, kinematic	:	101 cSt (40 °C / 104 °F)	
		11.50 cSt (100 °C / 212 °F)	
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	

SECTION 10. STABILITY AND REACTIVITY

PARAFLEX TM/MC HT 100



000003001345

_

Version 2.2		Revision Date 2019/09/17	Print Date 2019/09/17
Possibility of hazardous reac- tions	:	Hazardous polymerisation does not oc Stable under normal conditions.	cur.
Conditions to avoid	:	No data available	
Incompatible materials	:	Reactive with oxidising agents and red	ucing agents.
Hazardous decomposition products	:	May release COx, smoke and irritating to decomposition.	vapours when heated

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects				
Information on likely routes of exposure	:	Eye contact Ingestion Inhalation Skin contact		
Acute toxicity				
Product:				
Acute oral toxicity	:	Remarks: No data available		
Acute inhalation toxicity	:	Remarks: No data available		
Acute dermal toxicity	:	Remarks: No data available		
Components:				
Iubricating oils (petroleum), Acute oral toxicity	C2	20-50, hydrotreated neutral oil-based, high viscosity: LD50 (Rat): > 5,000 mg/kg,		
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist		
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,		
Skin corrosion/irritation				
Product:				
Remarks	:	No data available		
Serious eye damage/eye irritation				
Product:				
Remarks	:	No data available		
Respiratory or skin sensitisa	atio	on		
No data available				
Germ cell mutagenicity No data available				

PARAFLEX TM/MC HT 100

000003001345

Version 2.2



Print Date 2019/09/17

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure No data available

NO Gala avaliable

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available		
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available		
Toxicity to algae	:	Remarks: No data available		
Toxicity to microorganisms	:	Remarks: No data available		
Persistence and degradability				
Product:				
Biodegradability	:	Remarks: No data available		

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

PARAFLEX TM/MC HT 100

000003001345

Version 2.2



Print Date 2019/09/17

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm.		
The components of this product are reported in the following inventories:				
DSL	:	On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
EINECS	:	On the inventory, or in compliance with the inventory		
AICS	:	On the inventory, or in compliance with the inventory		
KECI	:	On the inventory, or in compliance with the inventory		
PICCS	:	On the inventory, or in compliance with the inventory		
IECSC	:	On the inventory, or in compliance with the inventory		


PARAFLEX TM/MC HT 100

000003001345

Version 2.2

SECTION 16. OTHER INFORMATION

Further information



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH NIOSH REL OSHA P0	:	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA		8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level;

PARAFLEX ^{™/MC} HT 100

000003001345

Version 2.2

Revision Date 2019/09/17

NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund

Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds United States, telephone: 1-800-268-5850; fax: 1-800-201- 6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date	:	2019/09/17

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN