

SAFETY DATA SHEET

DISTRIBUTED BY: R.E. CARROLL, INC. 1570 NORTH OLDEN AVENUE EXT. TRENTON, N.J. 08638-3204 USA T: 609-965-5211/800-257-9365 F: 609-695-0102 orders@recarroll.com

1. Identification

Product identifier

R-767

Other means of identification

None.

Recommended use

Designed for use in solvent and hot melt based adhesives, coatings, rubber and vinyl compounds,

printing inks, varnishes and can coatings.

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Resinall Corp

Address

302 N. Water Street

Severn, NC 27877

E-Mail

sds@ergon.com

Hours of Operation

8:00 a.m. - 5:00 p.m. (U.S. Eastern Time)

Emergency Number

1-800-634-6475

CHEMTREC

1-800-424-9300

2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Carcinogenicity

Category 2

Environmental hazards

Hazardous to the aquatic environment,

Category 3

long-term hazard

OSHA defined hazards

Combustible dust

Label elements



Signal word

Hazard statement

May form combustible dust concentrations in air. Suspected of causing cancer. Harmful to aquatic

life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Prevent dust accumulation to minimize explosion hazard. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. Observe good industrial hygiene practices.

Response

If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

May form combustible dust concentrations in air.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
HYDROCARBON PETROLEUM RESIN	V	Proprietary	99.4 - 100

Material name: R-767

Chemical name Common name and synonyms **CAS** number % 91-20-3 < 0.6 **NAPHTHALENE**

*New Jersey TSRN: 80100080-5077P

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

Dusts may irritate the respiratory tract, skin and eyes.

symptoms/effects, acute and

delayed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Indication of immediate medical attention and special treatment needed

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing media carefully to avoid creating airborne dust. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases

hazardous to health may be formed: Carbon monoxide and carbon dioxide.

Special protective equipment and precautions for

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

firefighters

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: R-767

SDS US 6537 Version #: 01 Issue date: 03-01-2019

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep at temperature not exceeding 49°C / 120°F. Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m3	
		10 ppm	
US. OSHA Table Z-3 (29 CFR			
Components	Туре	Value	Form
DUST	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit V	alues		
Components	Туре	Value	Form
DUST	TWA	3 mg/m3	Respirable particles
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
NAPHTHALENE (CAS 91-20-3)	STEL	7 5 mg/m3	
		15 ppm	
	TWA	50 mg/m3	
		10 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

NAPHTHALENE (CAS 91-20-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

NAPHTHALENE (CAS 91-20-3)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

Material name: R-767

SDS US

Individual protection measures, such as personal protective equipment

Eye/face protection Goggles/face shield are recommended.

Skin protection

Wear appropriate chemical resistant gloves. Nitrile or butyl rubber gloves are recommended. Hand protection

Other Wear appropriate clothing to prevent any possibility of skin contact with solutions containing 10%

or more of this chemical.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Solid.

Form Color Powder, Flakes, Clear to Amber.

Odor

Hq

Mild Odor

Odor threshold

Not available. Not available.

Melting point/freezing point

212 - 230 °F (100 - 110 °C)

Initial boiling point and

> 500 °F (> 260 °C)

Flash point

boiling range

>= 424.9 °F (>= 218.3 °C) Cleveland Open Cup

Evaporation rate

Not available.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure

Nil @ 200°F

Vapor density

0 (77 °F (25 °C))

Relative density

Not available.

Solubility(ies)

Solubility (water)

Negligible

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Explosive properties

Not explosive.

Oxidizing properties

Not oxidizing.

Percent volatile

< 0.6 % v/v

Specific gravity

1.08 - 1.09 (77 °F (25 °C))

Material name: R-767

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials. Minimize dust generation and accumulation.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact

Dust or powder may irritate the skin.

Eye contact

Dust may irritate the eyes.

Ingestion

May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity

Not expected to be acutely toxic.

Components NAPHTHALENE (CAS 91-20-3)

> **Acute** Dermal

LD50

Rabbit

Species

> 2 g/kg

Test Results

Skin corrosion/irritation

Serious eye damage/eye

irritation

Prolonged skin contact may cause temporary irritation.

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

NAPHTHALENE (CAS 91-20-3)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects. Not classified.

Specific target organ toxicity

- single exposure

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Material name: R-767

6537 Version #: 01 Issue date: 03-01-2019

SDS US 5/8

Product		Species	Test Results
R-767			
Aquatic		a)	
Crustacea	EC50	Daphnia	449.1945 mg/l, 48 hours estimated
Fish	LC50	Fish	1828.4058 mg/l, 96 hours estimated
Components		Species	Test Results
NAPHTHALENE (CAS 9:	L-20-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available.

Partition coefficient n-octanol / water (log Kow)

LC50

NAPHTHALENE

Fish

3.3

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours

13. Disposal considerations

Disposal instructions

Dispose in accordance with all applicable regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

NAPHTHALENE (CAS 91-20-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Material name: R-767

Yes

Hazardous chemical

Classified hazard categories

Combustible dust Carcinogenicity

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
NAPHTHALENE	91-20-3	<0.6	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to NAPHTHALENE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

NAPHTHALENE (CAS 91-20-3)

Listed: April 19, 2002

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

NAPHTHALENE (CAS 91-20-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

03-01-2019

Version #

01

Further information

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the

Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. None

known.

NFPA ratings

Health: 1 Flammability: 1 Instability: 0

List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.

TWA: Time Weighted Average Value.

Material name: R-767

SDS US

Disclaimer

Resinall cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States HazReg Data: International Inventories

GHS: Classification