## **Product Information**



1570 NORTH OLDEN AVENUE EXT. EWING, N.J. 08638-3204 USA T: 609-695-6211/800-257-9365 F: 609-695-0102 Orders@RECarroll.com

DISTRIBUTED BY: R.E. CARROLL, INC.

## **Ebonite H-150T**

## **DESCRIPTION**

**Cross Ebonite Oils** are asphaltic lubricant or compound for in the tyre industry and rubber compounding. The Ebonite series can also be used for multiple applications including greases, open gears, chains and inks applications.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C Viscosity, cSt @ 100° C	D-445 D-445			552.9 24.6
Viscosity, SUS @ 100° F Viscosity, SUS @ 210° F	D-2161 D-2161	90	140	3050 122.5
Gravity, API, 60° F Specific Gravity, 60/60° F Pounds per Gallon @ 60° F	D-4052 D-1250 D-1250	17.5 0.92	22.3 0.95 -	20.3 0.932 7.762
Flash, COC, °C (°F)	D-92	220 (430)		240 (460)
Pour Point, °C (°F)	D-97	<b>3</b>	-9 (+15)	-13 (+9)
Color	D-1500			BLACK
Fractions by Clay-Gel Absorption Asphaltenes Polars Aromatics Saturates	D-2007		- - - 60	1.0 5.48 37.49 56.03
DMSO Extraction, %	IP-346		3.0	2.2
PAH  Benzo (a) anthracene Benzo (a) pyrene Benzo (b) fluorantene Benzo (j) fluoranthene Benzo (k) fluoranthene Benzo (a) phenanthrene Dibenzo (a,h) anthracene Benzo (e) pyrene			10 ppm	7.582 0.204 0.579 0.585 0.585 ND 0.475 0.197 4.957

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ and Ebonite™ are trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

**CROSS OIL REFINING & MARKETING, INC.** 

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.crossoil.com