

orders@recarroll.com

SECTION 1: IDENTIFIE	CATION			
Sulfur, Pulverized Sulfur, Rubbermakers Sulfur, Commercial Sulfur				
Sulfur	Sulfur			
7704-34-9				
Element – Sulfur				
S ₈	31 1			
Rubber compounding, animal feed, various industrial applications				
None known. Keep away from heat sources, sparks, or open flames.				
Sales, Technical Service Georgia Gulf Sulfur Corporation P. O. Box 1165 Valdosta, Georgia 31603 Tel: (229) 244-0000 Fax: (229) 245-1664 http://www.georgiagulfsulfur.com	Shipping, Receiving Georgia Gulf Sulfur Corporation 1300 Spring Creek Road Bainbridge, Georgia, USA 39817 Tel: (229) 246-4552 Fax: (229) 246-3245 GPS Coordinates: 30° 54′ 06″ N 84° 36′ 30″ W			
CHEMTREC Tel: (800) 424-9300 within the USA Tel: 001-703-527-3887 outside the USA				
	Sulfur, Pulverized Sulfur, Commercial Sulfur Sulfur 7704-34-9 Element – Sulfur S ₈ Rubber compounding, animal feed, variation None known. Keep away from heat sour Sales, Technical Service Georgia Gulf Sulfur Corporation P. O. Box 1165 Valdosta, Georgia 31603 Tel: (229) 245-1664 http://www.georgiagulfsulfur.com CHEMTREC Tel: (800) 424-9300 within the USA			

GHS Information:

Classification: Skin Irritation, Category 2

OSHA Defined Hazards: Combustible Dust

GHS Label Elements

Pictogram (s):



Signal Word: Warning

Hazard Statement: May cause skin irritation. May form combustible dust concentrations in air.

SECTION 2: HAZARDS IDENTIFICATION (Cont.)

Hazard Statement	H290: May be corrosive to metals.			
	H303: May be harmful if swallowed.			
	H316: May cause mild skin irritation.			
	H320: May cause eye irritation.			
	H335: May cause respiratory irritation.			
Prevention Statement	P210: Keep away from heat/sparks/open flames/hot surfaces. No			
	smoking.			
	P220: Keep away from oxidizing agents.			
	P424: Use non-sparking tools when available.			
	P243: Take precautionary measures against static discharge.			
	P261: Avoid breathing dust/fume/gas/mist/vapors/spray.			
	P264: Wash hands thoroughly after handling and before eating.			
	P284: In case of inadequate ventilation, wear respiratory protection.			
Response Statement	P362: Take off contaminated clothing.			
	P363: Wash contaminated clothing before reuse.			
	P370+P378: In case of a fire, use water fog, spray, or regular foam to			
	extinguish. Do not use a direct water stream.			
	P381: Eliminate all ignition sources.			
Storage Statement	P402: Store in a dry place.			
	P403: Store in a well-ventilated place.			
	P404: Store in a closed container.			

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization

Mixture

Product	Percentage Contained	CAS Number
Sulfur	>99.5%	7704-34-9

Hazardous	Ingredient	None

	SECTION 4: FIRST AID MEASURES		
Description of First Aid Measu	ires		
Skin	Wash skin thoroughly with mild soap and water. Wash exposed clothing separately before reuse.		
Eye	Immediately flush eyes with plenty of water for 15 minutes, while holding upper and lower lid apart to insure rinsing of entire eye surface and lids. Do not use boric acid to rinse with. FOR SEVERE IRRITATION, SEEK MEDICAL ATTENTION, preferably an ophthalmologist		
Inhalation	Move victim to fresh air. Watch for signs of an allergic reaction. Use a bronchodilator inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, give artificial respiration. If heart has stopped beating, start cardiopulmonary resuscitation (CPR). SEEK MEDICAL ATTENTION.		
Ingestion	Give one tablespoon of <i>Syrup of Ipecac</i> to induce vomiting. If vomiting does occur, give fluids again. If vomiting has not occurred in twenty minutes, the same dose of <i>Syrup of Ipecac</i> may be repeated one additional time. Alternatively, vomiting may be induced by		

SECTION 4: FIRST AID MEASURES (CONT)

touching the back of the throat with a finger. Do not give anything by mouth to an unconscious or convulsing person. SEEK MEDICAL ATTENTION.

Most Important Symptoms and Effects (Long-Term and Acute)

Refer to Section 11: Toxicological Information

Indication of any Immediate Medical Attention or Special Treatment Needs

Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur

	SECTION 5: FIREFIGHTING MEASURES
Suitable Extinguishing Media	Water fog, spray, or regular foam. Do not use a direct water stream.
Unsuitable Extinguishing Media	Do not use solid streams of water, which could create sulfur dust clouds and cause an
	explosion or could move burning sulfur to adjacent areas.
Exposure Hazards	Prevent human exposure to smoke, fumes, or products of combustion (sulfur oxide gases). Evacuate nonessential personnel from the fire area. If large fire, evacuate people downwind from fire. Consider evacuation for ½ mile in all directions.
Advice for Firefighters	Firemen exposed to contaminated smoke should be immediately relieved and checked
	for symptoms of exposure of toxic gases. This should not be mistaken for heat
	exhaustion or smoke inhalation. Seek medical attention immediately!
Protective Equipment	Wear full-faced, self-contained breathing apparatus and full protective clothing.
Fire and Explosion Hazards	Fire will rekindle until mass is cooled below 310°F (154°C). Cool surrounding areas with water fog to prevent re-igniting. Sulfur dust is HIGHLY FLAMMABLE. If suspended in air, it will ignite by friction, static electricity, heat, sparks, or flames. Sulfur dust clouds may explode.
Combustion Products	Sulfur oxide gases
	SECTION 6: ACCIDENTAL RELEASE MEASURES
Personal Precautions	Minor spills such as torn or ruptured containers should be repaired or patched with tape if possible. Place spilled material in a disposable container. Avoid getting dust in eyes.
Protective Equipment	Maintain adequate ventilation. Wear a dust mask when dust is present or a respirator if smoke is present. Wear safety glasses.
Emergency Procedures	As an immediate precautionary measure isolate spills or leak areas. Eliminate all sources of ignition, such as flares, sparks, or flames, in the immediate area. No smoking. Ventilate closed spaces before entering.
Environmental Precautions	Do not allow runoff to enter lakes or waterways.
Containment/Cleanup Measures	Gently sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking, to avoid creating a dust cloud. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean-up is

complete.

	SECTION 7: STOPAGE AND HANDLING			
SECTION 7: STORAGE AND HANDLING Precautions for Safe Handling All handling and conveying equipment should be properly grounded and bonded. Be on to create dust. Avoid any conditions that might tend to create a dust explosion. Magood housekeeping practices to minimize dust build-up and dispersion. Eliminate sour ignition. Keep away from heat, sparks, and flames. Use nonferrous tools, when available reduce sparking. Gently sweep or shovel up spilled materials using a natural fiber broom a aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.				
Conditions for Safe Storage, Including Cor Sto chl				
-	Keep away from flammable materials, sources of heat, flame, sparks, chlorates, nitrates and other oxidizing agents.			
SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION			
Engineering Measures/Controls	Maintain adequate ventilation in all areas. No flares or flames in area. Be careful not to create dust. Eliminate sources of ignition.			
Personal Protective Equipment				
Pictograms				
Respiratory	Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits.			
Eyes/Face	Wear suitable, protective safety glasses to prevent eye irritation from dust.			
Hands	Wash hands thoroughly after handling and before eating or smoking.			
Skin/Body	Wear suitable, protective clothing to prevent skin irritation from dust. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing separately before reuse.			
Environmental Exposure Controls	Follow best practice for site management and disposal of waste. Avoid release to the environment.			
General Industrial Hygiene Considera	tions Protective equipment should be used in any situation that may result in hazardous exposure. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Use nonferrous tools to reduce sparking Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shove to prevent sparking. Maintain adequate ventilation in all areas.			

Physical State	Solid, powder form
Appearance	Yellow powder
Formula	S ₈ (Rhombic or monoclinic)
Odor	Odorless, or faint odor of rotten eggs
Odor Threshold	No data available
pН	No data available
Boiling Point	832° F (444° C)
Melting/Freezing Point	118-120°C (244-248°F)
Flash Point	207°C (405°F) Closed Cup

Upper: 6.38% (v) Lower: 0.17% (v)

May form combustible dust concentrations in air

8mmHg at 246°C (475°F) 1mmHg at 183.8°C (362.8°F)

No data available

No data available

Does not decompose

99.5% Min.

240°C (464°F)

Not applicable

Flammability

Vapor Pressure

Vapor Density

Purity

Viscosity

Evaporation Rate

Flammable/Explosion Limits

Auto-Ignition Temperature

Decomposition Temperature

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

2.07 @ 70° F			
Insoluble			
Powder: 33-80 lbs. /ft ³			
SECTION 10: STABILITY AND REACTIVITY			
Stable			
Keep from heat sources, sparks, and open flames. Minimize dust generation and accumulation.			
Incompatible Materials Oxidizing agents, copper, copper alloys, steel, chlorates, nitrates			
ions Oxidizing agents may react violently			
Oxides of sulfur gases produced by burning sulfur			
Will not occur			

	SECTION 11: TOXICOLOGICAL INFORMATION
Likely Routes of Exposure	Inhalation, ingestion, skin contact, and eye contact
Signs and Symptoms of Overexposure	Nose or throat irritation, coughing, chest discomfort, asthma, difficulty breathing, nausea, vomiting, stinging eye irritation, skin irritation, hives.
Exposure Limits	No exposure limits have been established
Acute Symptoms and Effects Inhalation	Prolonged inhalation may cause irritation of respiratory tract. Breathing of dust may aggravate asthma and other pulmonary diseases.
Eye Contact	Sulfur dust is an eye irritant.
Skin Contact	No adverse effects; however, skin irritation may be aggravated in persons with existing skin lesions.
Ingestion	Ingested sulfur is converted to sulfides in the gastrointestinal tract, and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Swallowing large amounts may cause nausea and vomiting.

	SECTION 11: TOXICOLOGICAL INFORMATION (CONT)				
Long-Term Effects	None know	wn to humans			
Toxicity	LD ₅₀	Oral: >5050 mg/kg (rats)			
	Dermal: >2020 mg/kg (rats)				
	LC ₅₀	Inhalation @ 90%: >5.49-mg/L air concentration (rats)			
	Skin	Slightly irritating (rabbits)			
	Eye	Minimal irritation in non-washed eyes (rabbits)			
<u>S</u> (ensitization	Reproductive Effects	Developmental Effects	Endocrine Disruptor	
No	t Established	Not Established	Not Established	Not Established	
	iii+	Tana		NA uto conicitu	
	Carcinogenicity	ngredient designated by NTP	togenicity	Mutagenicity	
	SECTI	ON 12: ECOLOGICAL	INFORMATION		
Toxicity					
Toxicity Toxicity to fish	LC50- Oncorhynch	us mykiss (rainbow trout) ->			
•		us mykiss (rainbow trout) ->			
•	LC50- Oncorhynch LC50- other fish- 80	us mykiss (rainbow trout) ->	180 mg/l -96h		
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates	LC50- Oncorhynch LC50- other fish- 80	us mykiss (rainbow trout) -> 66 mg/l -96h	180 mg/l -96h		
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates Ecotoxicity Mobility	LC50- Oncorhynchu LC50- other fish- 80 EC50- Daphnia mau No data available No data available	us mykiss (rainbow trout) -> 66 mg/l -96h	180 mg/l -96h		
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates Ecotoxicity Mobility Degradation	LC50- Oncorhynchi LC50- other fish- 8 EC50- Daphnia maj No data available No data available No data available	us mykiss (rainbow trout) -> 66 mg/l -96h	180 mg/l -96h		
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates Ecotoxicity Mobility Degradation Bioaccumulation	LC50- Oncorhynchu LC50- other fish- 80 EC50- Daphnia may No data available No data available No data available No data available	us mykiss (rainbow trout) -> 66 mg/l -96h gna (Water flea) -> 5,000 mg	180 mg/l -96h ;/l -48h		
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates Ecotoxicity Mobility Degradation Bioaccumulation Results of PBT and	LC50- Oncorhynchu LC50- other fish- 80 EC50- Daphnia may No data available No data available No data available No data available	us mykiss (rainbow trout) -> 66 mg/l -96h	180 mg/l -96h ;/l -48h	quired/not conducted	
Toxicity to fish Toxicity to Daphnia And Other Aquatic Invertebrates Ecotoxicity Mobility Degradation Bioaccumulation	LC50- Oncorhynchu LC50- other fish- 80 EC50- Daphnia may No data available No data available No data available No data available	us mykiss (rainbow trout) -> 66 mg/l -96h gna (Water flea) -> 5,000 mg	180 mg/l -96h ;/l -48h	quired/not conducted	

Waste Treatment Methods Product Waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging Waste Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

SECTION 14: TRANSPORTATION INFORMATION

Solid sulfur is not regulated if transported in non-bulk packaging (less than 400kg per package) or if formed to a specific shape, such as prills, granules, pellets, pastilles, or flakes (49 CFR 172.102, special provision 30).

US and Canadian Shipments

Bulk containers (packaging) of powdered sulfur of more than 400 kg (880 lbs.) per package

	14.1 UN	14.2 UN proper	14.3 transport hazard	14.4 packaging	14.5 environmental
	number	shipping name	class(es)	group	hazards
DOT	NA1350	Sulfur (Sulphur)	9 (Misc. Hazardous	III	No data available
(Domestic)			Materials)		
DOT	UN1350	Sulphur (Sulfur)	4	111	No data available
(International)					
TDG	UN 1350	Sulfur	4.1	III	No data available

SECTION 14: TRANSPORTATION INFORMATION (CONT.)

Other than US and Canadian Shipments

All shipments of powdered sulfur

IMO/IMDG	UN1350	Sulphur (Sulfur)	4.1 (flammable solid)	III	No data available
IATA/ICAO	UN1350	Sulfur	4.1	111	No data available

This product is not a Marine Pollutant as defined in 40 CFR Part 172.

Pictograms for Hazard Classes

Powdered sulfur packaging over 400 kg (880 lbs.) only



Special Precautions for User

None specified

	SECTION 15: REGULATORY INFORMATION			
TSCA	This product is listed on the TSCA Inventory at CAS Registry Number 7704-34-9.			
CERCLA	 Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) If this product is accidentally spilled, it is not subject to any special reporting. We recommend that you contact state and local authorities to determine if there are other local reporting requirements. 			
SARA TITLE III	Superfund Amendments and Reauthorization Act, Title III			
	• Sections 311/312: None. Section 313: None. Section 302: None.			
RCRA	Resource Conservation and Recovery Act			
	 Not subject to reporting because sulfur is not identified as a hazardous waste. 			
	SECTION 16: OTHER INFORMATION			
Last Revision Date	08/29/2018 Preparation Date 05/01/2015			
Additional Information	For additional information, contact your technical sales representative. For additional health and safety information, call Georgia Gulf Sulfur Corporation at 229-244-0000.			
Disclaimer/				
Statement of Liability	THE INFORMATION CONTAINED HEREIN IS BASED ON THE PRESENT KNOWLEDGE AND			
	DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, GEORGIA GULF SULFUR			
	CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF			
	THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. FURTHERMORE, THIS SHALL NOT CONSITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT			
	ESTABLISH AND LEGALLY VALIDIFY A CONTRACTUAL RELATIONSHIP. GEORGIA GULF SULFUR			
	CORPORATION ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT			
	DESCRIBED HEREIN.			