



R.E. Carroll, Inc.

Raw Materials • Fillers • Petroleum Products



Ethylene	KP KEP Series	Product
Propylene	ISO 9001	Data
Rubber	ISO 14001 Certified by DNV-QA	Sheet

KEP-240

Features :

- High vulcanization speed
& good roll processibility
- Used for general purpose
- Particularly suitable for weather strip solid

Characteristics :

Ethylene Content : low
Cure Speed : fast
Molecular Weight Distribution : medium
Oil extension : -
Specific Gravity : 0.86

Applications :

Automobile parts, Injection molding goods
and Various types of Industrial parts.

Test Items	Sales Specifications	Test Methods
Volatile Content (%)	0.75 max	ASTM D1416
Ethylene Content (wt.%)	56.5 ± 3.5	ASTM D3900
ENB content (wt.%)	4.5 ± 1.0	ASTM D6047
Oil content (PHR)	-	Internal
Raw Mooney Viscosity (ML1+4,125°C)	42.0 ± 6.0	ASTM D1646

(Polymer remassed at 140°C)

Last updated Feb. 9, 2000

Revision No.	2
--------------	---

S.B. KIM / Manager,

R&D Center

KUMHO POLYCHEM Co., Ltd.

CALCIUM CARBONATES • CLAYS • SOLVENTS • ZINC OXIDE • WAXES • ZINC DUST • PLASICIZERS • CHEMICAL SPECIALTIES
LUBRICANTS • PROCESS OILS • ALUMINA TRIHYDRATE • MAGNESIUM CARBONATE • MAGNESIUM OXIDES

Quotations unless otherwise noted subject to prior sales and change without notice

CONTROLLED COPY
Valid Only If In Red

DO NOT REMOVE
"Master Copy"